



Sample photo

Order symbol: PC F 85 T
Product nbr: 8724012
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074002204
EI. number:
 Finland 3423515
 Denmark 8212001640
 Italy 7202045
 Sweden 2536853

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:		L	W	H	Rating:		
mm:		230	80	85	Ingress Protection (EN 60529): IP 66/67		
inch:		9.1	3.1	3.3	Impact Resistance (EN 50102): IK 08		
Materials:						Electrical insulation: Totally insulated	
Material:		PC				Halogen free (DIN/VDE 0472, Part 815): Yes	
Base colour:		RAL 7035				UV resistance: UL 508	
Cover colour:		Clear transparent				Flammability Rating (UL 746 C 5): UL 94 5V	
Cover screws material:		Polyamide				Glow Wire Test (IEC 695-2-1) °C: 960	
Cover screws colour:		Grey				NEMA Class: NEMA 1, 4X, 6, 6P, 12, 13	
Gasket material:		Polyurethane				Certificates:	
Temperatures:						Germanischer Lloyd (GL)	
Short term:		-40 ... 120 °C				Underwriters Laboratories	
Continuous:		-40 ... 80 °C				Canadian Standards Association	
Short term:		-40 ... 250 °F				Fimko	
Continuous:		-40 ... 175 °F				Europe EN 50298 1998	
Accessories:						UL Canada	
F-MP		Mounting plate				Gost R	
FM-3		DIN-35 Mounting rail					
FP 22040		Mounting foot kit (2 pcs)					

