## LINEAR MODE DC POWER SUPPLY SINGLE OUTPUT SERIES





0~30V/0~10A 0~60V/0~5A 0~30V/0~20A 0~60V/0~10A



#### ► Introduction

The TP300W/600W series are linear DC power supplies with 1 channel, 300W/600W output. In constant voltage and current operations, the power supply provides high regulation and low ripple & noise. The output ON/OFF control and coarse/fine control enables safe and easy operation. The TP300W/600W series are widely used in applications of powering operational amplifier, push pull stages, logic circuit and definition systems.

#### **▶** Features

- Constant voltage and constant current operations
- Auto CV and CC switch
- Output ON/OFF control
- Preset function, setting of voltage and current with output open circuit (TP-3020/6010)
- High efficiency, light and compact design
- High power density
- Over load and reverse polarity protections
- Dual-color two digital panel meters

# LINEAR MODE DC POWER SUPPLY SINGLE OUTPUT SERIES

### ► Specifications

Model	TP-3010	TP-6005	TP-3020	TP-6010			
Constant voltage operation							
Line regulation	≤0.01%+5mV	≤0.01%+5mV	≤0.01%+10mV	≤0.01%+5mV			
Load regulation	≤0.02%+5mV	≤0.02%+5mV	≤0.02%+10mV	≤0.02%+5mV			
Ripple & Noise (5Hz~1MHz)	≤3mVrms						
Constant current operation							
Line regulation	≤0.2%+3mA						
Load regulation	≤0.2%+3mA (I≤3A) ≤0.2%+5mA (I>3A) ≤0.2%+15mA (I≥10A)						
Ripple & Noise (5Hz~1MHz)	≤3mArms (I≤3A) ≤10mArms (I>3A)						
Display							
Accuracy	Real voltage and current output: ±(1% reading+2 digits)						
	Preset voltage and current: ±(1% reading+8 digits)						
General							
Operating environment	0°C~40°C, ≤80%RH						
Storage environment	-10°C~70°C, ≤70%RH						
Power source	AC110V/220V±10%, 50/60Hz						
Accessories	Power cord x1, Operation manual x1, Test lead x1 Power cord x1, Operation manual x1						

### ► Selection Guide

Model	TP-3010	TP-6005	TP-3020	TP-6010
Output voltage	0~30V	0~60V	0~30V	0~60V
Output current	0~10A	0~5A	0~20A	0~10A
Voltmeter	3 digits LED	3 digits LED	3 digits LED	3 digits LED
Ammeter	4 digits LED	3 digits LED	3 digits LED	4 digits LED
Resolution	100mV/10mA	100mV/10mA	100mV/100mA	100mV/10mA
Fixed output				
Preset V&I			√	√
Output ON/OFF	√	√	√	√
Dimension (WxHxD)	255x155x370mm		255x155x330mm	
Weight	10kg	10kg	14kg	14kg