



RoHS Compliance



5	CONTACT	P B S	2	Ag PLATED	6	SPRING	P B S	1	
3	TERMINAL	BRASS	10	Ag PLATED	4	TERMINAL BASE	PHENOL RESIN	1	NATURAL
1	FRAME	S P C C	1	Ni PLATED	2	KNOB	P O M	1	G 2-8
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED	SPECIFICATION	TITLE: SLIDE SWITCH (2P3T)							
	RATING: DC 30V 0.3A	MODEL NO: SS-23D03 (G)							
	CONTACT RESISTANCE: 30mΩ max.	TOLERANCE	UNIT: MM	DWN.					
	INSULATION RESISTANCE: 500MΩ at 500V DC	UP TO 1.0:±0.1	SCALE: 4:1	CHK'D.					
	WITHSTAND VOLTAGE: AC 500V for 1 minute	1.0 TO 10.0:±0.2	VERSION: 01	APPD.					
	OPERATION FORCE: REFER ATTACH SPECIFICATION	OVER 10.0:±0.3	DRWG NO: 1						
SWITCHING LIFE: 10K cycles min.									

BY: DATE: 04-DEC-2002

Green Electronics CO.,LTD

